

# MEGALUBE

## MOTOR HD SAE 30

### Application areas:

**MOTOR TURBO HD SAE 30** is a mono-grade HD motor oil for Diesel and Petrol motors. Including hard working turbo-charged and naturally aspirated diesel engines. It can also be used for the lubrication of piston compressors and as hydraulic oil in accordance with the manufacturers protocol.

### Characteristics:

**MOTOR TURBO HD SAE 30** offers full lubrication even at high temperatures. It also offers very good wear protection. Excellent cleanliness of motor (reduces the formation of the sludge).

- Full lubrication ability even at high temperatures.
- Optimal wear protection
- Excellent cleanliness of motor (no sludge)
- It is suitable for catalysts
- Very good protection on wear on the Bore.

### Specifications & Approvals:

- ACEA E2	- MB 227.0
- API : SL / CF 4	- MIL-L-2104 D
- MAN 270	- MIL-L-46152 B
- VOLVO VDS	- CCMC D2/G2
- CATERPILLAR TO-2	- MACK EO
- ALISON C-4	

### Data:

Density at 20 °C	g/cm <sup>3</sup>	0,87 –0,89
Pour point	°C	-30 to –10 (depending on SAE class)
TBN	mg KOH/g	11
Sulphated Ash	%	1,3
SAE Class availability		10W,10W20,20W20,30,40,50

### Transport:

ADR/SDR

Not dangerous goods

### Disposal:

VVS-Code

### Toxicity:

Toxic Class  
BAG T Nr

Free  
617 200