

# MEGALUBE

## MOTOR OIL SAE 15W40 CF-4/SL

**Application:** All diesel and petrol motors with and without turbo chargers.

**Characteristics:**

- Reliable cold start, all year.
- For high sensitive motors.
- Optimal anti-wear characteristics.
- 15W/40 is guaranteed for the full oil change period (stay-in-grade).
- Very high motor cleanliness (stops sludge-formation).
- Economical because of long oil change intervals.
- Excellent protection against bore polishing.
- Guarantees excellent oxidations –and heat stability.
- Full lubrication properties, also at high temperatures.

**Specifications & Performance profile:**

ACEA E3 API CF 4/SL Daimler-Benz 228.1 MAN 271 VOLVO VDS ALISON C-4 MTU MACK EO-K2 CATERPILLAR TO-2 CUMMINS NTC 400 MIL-L-2104 E VW 505	Covers all the old specs. CC, CD, CE, CF, CF-4 227.1, 228.0 CCMC D4/D6 MIL-L-2104D/E/F MAN QC13-017
--	--

**Data:**

Density at 20 °C	g/cm <sup>3</sup>	0.886
Viscosity at – 15 °C	mPa.s	3360
Viscosity at 100 °C	mm <sup>2</sup> /s	14.6
Viscosity at 150 °C	mPa.s	3.92
Pour point @ °C	°C	-30
TBN	mgKOH/g	11,0
Sulphate Ash	%	1.30

**Transport:**

ADR/SDR

Not Dangerous Goods

**Disposal:**

VVS-CODE:

1470 (Switzerland)

**Toxicity:**

Toxic Class:

Free

BAG-T NR:

611500