

MEGALUBE

SUPER MOTOR OIL SAE 15W40 CH-4/SL

HIGH PERFORMANCE MOTOR OIL

Application:

SUPER MOTOR OIL SAE 15W40 is used for all 4-stroke petrol and diesel motors (with and without) turbo charges. It is high performance multi-grade oil for a mixed fleet of trucks, cars and machinery.

Specification and Classification Characteristics:

SUPER MOTOR OIL SE 15W40 is extra ordinary multi purpose and multi-grade motor oil, based on high quality base oils. With a cleverly designed additive combination of the highest and newest quality. It has also guarantees very low oil consumption and gives extended oil change intervals (Stay-in-grade). **SUPER MOTOR OIL SAE 15W40** has got highly working detergent and dispersant additives to prevent residue formation and to neutralize acidulous products. The product is very oxidation resistant, lubricates exceptionally well and it reduces wear. The high performance motor oil is compatible with all well-known motor oils. **SUPER MOTOR OIL SAE 15W40**, guarantees clean motors and reduces oil storage problems.

Specification:

ACEA A3/B3/B4/E3/E5	Covers also the following old Norms
API SL / CH-4	SE, SF,SG,SH,SJ / CC, CD, CE,CF,CG4
MB 229.1/228.2 /228.3	MB 226,1 226,9 227,1
VOLVO VDS-2	CCMC G4/G5/D4/D5/PD2
VW 505.00	
MAN 271/M 3275	MIL-L-2104D/E
ALLISON C-4	MIL-L-46152 B/C
MTU MTL 5504 TYPE 2	
MWM KD Motoren	
RVI RLD	
MACK EO-M Plus	
Cummins CES 20,072/1/6/7/8	
ZF TE-ML 02C/03A+/04B/04C/07C	

Data:

SAE Grade		15W40
Density at 20 °C	g/cm ³	0,883
Viscosity at -15 °C	mPa.s	3350
Viscosity at +100 °C	mm ² /s	14,2
Viscosity Index		140
Pour Point	°C	-36
Sulphate Ash	%	1,36
TBN	Mg KOH/g	10.6
Flame Point	°C	221