

# MEGA LUBE

## HEAVY DUTY PLUS SAE 15W40

### HIGH PERFORMANCE MOTOR OIL

#### Application:

**HEAVY DUTY PLUS SAE 15W40** is used for all 4-stroke petrol and diesel motors with and without turbo charges. It is a high performance multi-grade oil for a mixed fleet of trucks, cars and machinery. Specifically designed for the latest electronically controlled diesel engines experiencing high soot loading.

#### Specification and Classification Characteristics:

**HEAVY DUTY PLUS SAE 15W40** is an extra ordinary multi-purpose and multi-grade motor oil, based on high quality base oils, with a cleverly designed additive combination of the highest and latest technology. It also guarantees very low oil consumption and gives extended oil drain intervals (Stay-in-grade). **HEAVY DUTY PLUS SAE 15W40** has hard working detergent and dispersant additives to prevent residue formation and to neutralize acidulous products. The product is very oxidation resistant, lubricates exceptionally well and reduces wear. The high performance motor oil is compatible with all well-known motor oils. **HEAVY DUTY PLUS SAE 15W40**, guarantees clean motors and reduces oil consumption.

#### Specification:

ACEA E7-04	Covers also the following old Norms
API : CI 4 PLUS / SL	SE, SF, SG, SH, SJ / CD, CE, CF-4, CG-4, CH-4
MB 228.3	<b>MB-APPROVAL 228.3</b>
VOLVO VDS-3	CCMC G4/G5/D4/D5/PD2
VW 505.00	
MAN 271/M 3275	MIL-L-2104D/E
ALLISON C-4	MIL-L-46152 B/C
MTU MTL 5504 TYPE 2	<b>APPROVED</b>
MWM KD Motoren	
RVI RLD 99	
MACK EO-M Plus	
Cummins CES 20078	<b>APPROVED</b>
ZF TE-ML 02C/03A+/04B/04C/07C	

#### Data:

SAE Grade		15W40
Density at 20 °C	g/cm <sup>3</sup>	0,883
Viscosity at -15 °C	mPa.s	3350
Viscosity at 100 °C	mm <sup>2</sup> /s	15,2
Viscosity Index		140
Pour Point	°C	-36
Sulphate Ash	%	1,36
TBN	Mg KOH/g	11
Flame Point	°C	221