

MEGALUBE



MOTOR OIL SAE 20W50 SL/CH-4

Application: All diesel and petrol motors with and without turbo chargers.

Characteristics:

- Reliable cold start, all year.
- For high sensitive motors.
- Optimal anti-wear characteristics.
- 20W/50 is guaranteed for the full oil change period (stay-in-grade).
- Very high motor cleanliness (stops sludge-formation).
- Economical because of long oil change intervals.
- Excellent protection against bore polishing.
- Guarantees excellent oxidations –and heat stability.
- Full lubrication properties, also at high temperatures.

Specifications & Performance profile:

ACEA E7 API CH- 4/SL Daimler-Benz 228.3 MAN 271 VOLVO VDS 3 ALISON C-4 MTU MACK EO-K2 CATERPILLAR TO-2 CUMMINS NTC 400 MIL-L-2104 E VW 505	Covers all the old specs. CC, CD, CE, CF, CF-4 CG-4 227.1, 228.0 CCMC D4/D6 MIL-L-2104D/E/F MAN QC13-017
---	---

Data:

Density at 20°C	g/cm ³	0.886
Viscosity at 40 °C	mm ² /s 122-147	135
Viscosity at 100°C	mm ² /s 17-22	19
Viscosity at 150°C	mm ² /s	5.92
Pour point @ °C	°C	-30
TBN	mgKOH/g	11,0
Sulphate Ash	%	1.30

Transport:

ADR/SDR

Not Dangerous Goods

Disposal:

VVS-CODE:

1470 (Switzerland)

Toxicity:

Toxic Class:

Free

BAG-T NR:

611500