

# MEGA LUBE

## WINCH GEAR GREASE

**Characteristics:** **WINCH GEAR GREASE** contains special additives to provide extreme pressure properties for extra protection against wear and heavy shock loads.

This grease has good resistance to heat, outstanding mechanical stability especially under high shear condition and retains the lubrication ability and protection even in the presence of or mixed with water.

This grease meets and exceed SKF Emcor washout test and can be described as a multi service grease.

**Application:** **WINCH GEAR GREASE** is designed primarily for winch gear boxes and is suitable for all types of anti-friction and plain bearings, including those subjected to oscillatory movement through limited angles. Due to the good adhesiveness, it is also suitable for components such as open gears, cams, slides, etc.

**Specifications:** **Conforms to SABS 1851**

**Data:**

NLGI	00	0	1	2	3
SOAP	CALCIUM COMPLEX POLYMER				
Oil viscosity @ 40 °C	170 cSt	170 cSt	170 cSt	170 cSt	170 cSt
Ball EP Properties KG	350	350	350	350	350
Worked penetration @ 25 °C	400 –430	355 –385	310 –340	265 – 295	265 – 295
Operating range °C	-30 °C to 160 °C	-30 °C to 160 °C	-30 °C to 160 °C	-20 °C to 160 °C	-20 °C to 160 °C
Drop point °C (D566)	>250 °C	>250 °C	>250 °C	>250 °C	>250 °C

**Features:**

- ❖ **Universal grease**
- ❖ **Longer component life even in the presence of water**
- ❖ **Excellent temperature stability**
- ❖ **Economical**
- ❖ **Good pump ability**
- ❖ **Adhesive**
- ❖ **Lead free**

**Transport:** Not dangerous

**Disposal:** Disposal of as Country legislate

**Toxity:** Toxic class: FREE