

MEGA LUBE

HIGH TECH HIGH PERFORMANCE MOTOR OILS FULL SYNTHETIC SAE 10W 40

Application: For all HIGH PERFORMANCE 4-stroke Petrol and Diesel motors, with or without turbo chargers (for delivery trucks, kombi's and working vehicles).

Characteristics:

- Synthetic.
- Reliable on cold starts due to a low viscosity and optimal lubrication.
- Withstands extreme influences even at high temperatures.
- Stay-in-grade-oil.
- Less friction.
- Prevents sludge deposits.
- Economical due to long oil change intervals.
- Saves fuel up to 5% and therefore reduces the exhaust emissions.
- Compatible with all other high quality well known engine oils.

Specifications & Performance profile:

API SM /CI-4 PLUS ACEA E5-02 MAN 3275 VDS-3 CUMMINS 20078 MB 229.3 VW 505.00 / 505.01 (level) FEO Fuel Economy Oil	Covers all the old specs. SE, SF, SG,SH,SJ,SL/ CC, CD,CE,CF-4,CG-4,CH-4
---	---

Data:

		SAE 10W 40
Colour		Yellow brown
Density at 20°C	g/cm ³	0.865
Viscosity at -20°C	mPa.s	3350
Viscosity at 100°C	mm ² /s	15.5
Viscosity Index		176
Pourpoint	°C	-33
TBN/Total Base Number	mgKOH/g	10,7
Sulphate Ash	%	1.05
Flash point	°C	232