

# MEGA LUBE

## HIGH PERFORMANCE SEMI-SYNTHETIC MOTOR OIL SAE 10W 40

**Application:** For all 4-stroke Petrol, Diesel motors, with or without turbo chargers (for delivery trucks, kombi's and working vehicles).

**Characteristics:**

- Semi-Synthetic.
- Reliable on cold starts due to a low viscosity and optimal lubrication.
- Withstands extreme influences even at high temperatures.
- Stay-in-grade-oil.
- Less friction.
- Prevents sludge deposits.
- Economical due to long oil change intervals.
- Saves fuel up to 5% and therefore reduces the exhaust emissions.
- Compatible with all other high quality well known engine oils.

**Specifications & Performance profile:**

ACEA A3/B3 E7 API SL/CI-4 VDS-3 CUMMINS 20078 MAN 3275 MB 229.1 VW 500.00 / 505.01 (level) FEO Fuel Economy Oil	Covers all the old specs. SE, SF, SG,SH,SJ / CC, CD,CE,CF-4,CG-4
--	--

**Data:**

		10W/40
Colour		Brown
Density at 20 °C	g/cm <sup>3</sup>	0.865
Viscosity at -20 °C	mPa.s	3350
Viscosity at 100 °C	mm <sup>2</sup> /s	14.5
Viscosity Index		136
Pour point	°C	-33
TBN/Total Base Number	mgKOH/g	9,7
Sulphate Ash	%	1.25
Flash point	°C	222